

DPC-3080S

8", 5 Wire Resistive Touch , Intel BayTrail J1900 , Ture-Flat Panel PC



Features

- 8" LED backlight LCD and Resistive touch panel
- Fanless design, Front Panel IP65
- Embedded Intel Celeron J1900(2.0GHz) processor
- 1 COM,2 USB, 2 GbE, HD Audio, VGA, HDMI
- Panel and VESA mounting



Specifications

System	
CPU	Intel® Quad-Core Celeron J1900 (2.0GHz)
Memory	DDR3L 4GB
Storage	1 x Full-size Mini-PCIe for mSATA SSD
Operating System	Windows 7/8.1/10
Display	
Size	8-inch
Resolution	1024 x 768
Viewing Angle (H/V°)	80/80/80/80
Brightness	400 cd/m ²
Backlight	LED
LED Lifetime	30000 hrs
VGA	Up to 2560 x 1600
HDMI	Up to 1920 x 1080
Multi-Display	Dual display (LVDS + VGA/HDMI)
Touchscreen	
Type	5-Wire Analog Resistive Touch
Transparency	80%
Hitting life	35 million times
Surface hardn	≥3H
I/O Connectors	
Series Port	1 x RS-232/485
USB Port	1 x USB3.0 1 x USB2.0
LAN Port	2 x GbE LAN
Display Port	1 x HDMI、1 x VGA
Audio	1 x Line-out

Others	
	1 x DC-IN (2-Pin Phoenix) 1 x Remote switch connector 1 x ATX Power Switch
Expansion	
Mini-PCIe	1 x Full-size Mini-PCIe for mSATA 1 x Full-size Mini-PCIe
Power Management	
Power Input	DC 12V
Power Adapter	AC-DC, 12V@5A, 60W
Power Consumption	29W(Typ.)
Environmental	
Operating Temperature	-10~50°C
Storage Temperature	-20~60°C
Relative Humidity	10%-90%,@ 40°C (non-condensing)
Vibration protection	5~500Hz, 0.026 G ² /Hz, 2.16 Grms, X, Y, Z, 1 hour per axis
Certifications	CE, FCC
Mechanical	
Housing	Aluminum alloy panel, all-metal structure
Mounting	Panel-mount, VESA-mount
Dimension (W x L x H)	227 x 173x47 mm
Weight	1.7Kg
Packing List	
	1 x DPC-3080S 1 x AC-DC Power Adapter 1 x Certificate 1 x Warranty Card 8 x Panel Mounting Buckles

Dimensions

