

# DPC-6152

15", Capacitive Projection Touch Screen, Intel Skylake Core I5-6200U, Ture-Flat Panel PC



## Features

- 15" LED backlight LCD and Capacitive touch panel
- Fanless design, Front Panel IP65
- Intel®Skylake Core I5-6200U(2.3GHz) processor
- 2 COM, 4 USB, 2 GbE, HD Audio, VGA, HDMI
- Panel and VESA mounting



## Specifications

System	
CPU	Intel Skylake Core I5-6200U (2.3GHz)
Memory	2 x SO-DIMM DDR4-2133 (Up to 32GB)
Storage	1 x 2.5" Driver Bay for SATA HDD/SSD 1 x Full-size Mini-PCIe for mSATA SSD
Operating System	Windows 7/8.1/10
Display	
Display Type	15" TFT LED
Viewing Angle (H/V°)	89/89/89/89
Size	15-inch
Resolution	1024 x 768
Brightness	350nits
Contrast Ratio	1000:1
Backlight	LED
LED Lifetime	50000 hrs
VGA	Up to 2560 x 1600
HDMI	Up to 1920 x 1080
Multi-Display	Dual display (LVDS + VGA/HDMI)
Touchscreen	
Type	Projected Capacitive Touch
Transparency	87%
Surface hardness	≥6H
I/O Connectors	
Series Port	2 x RS-232 (COM1/2)
USB Port	2 x USB3.0 2 x USB2.0
LAN Port	2 x GbE LAN
Display Port	1 x HDMI, 1 x VGA
Audio	1 x Line-out, 1 x Mic

Others	
	1 x DC-IN (2-Pin Phoenix) 1 x Remote switch connector 1 x ATX Power Switch
Expansion	
Mini-PCIe	1 x Full-size Mini-PCIe for mSATA 1 x Full-size Mini-PCIe
Power Management	
Power Input	DC 12V(9~36V Optional)
Power Adapter	AC-DC, 12V@5A, 60W
Power Consumption	25W(Typ)
Environmental	
Operating Temperature	-10~50°C
Storage Temperature	-20~60°C
Relative Humidity	10%-90%, @ 40°C (non-condensing)
Vibration protection	5~500Hz, 0.026 G <sup>2</sup> /Hz, 2.16 Grms, X, Y, Z, 1 hour per axis
Certifications	CE, FCC
Mechanical	
Housing	Aluminum alloy panel, all-metal structure
Mounting	Panel-mount, VESA-mount
Dimension (W x L x H)	370 x 294 x 65mm
Weight	4.2Kg
Packing List	
	1 x DPC-6152 1 x AC-DC Power Adapter 1 x Certificate 1 x Warranty Card 8 x Panel Mounting Buckles

## Specifications

