

DPM-1156G

15.6 ", capacitive touch screen Industrial touch display



Features

- 15.6" LCD, capacitive touch
- Compact structure, front panel IP65 dustproof and waterproof
- All-metal structure design, solid and durable
- Support panel and VESA installation
- 1000 lumen display,
- Touch screen surface AG AF treatment



Specifications

Display

Size	15.6-inch
Resolution	1920*1080
Viewing Angle	85/85/85/58
Color Support	16.7M
Brightness	1000 cd/m ²
Contrast Ratio	800:1
Response Time	3/0 (Typ.)(Tr/Td) ms
Backlight	LED
Backlight Life	50000 h

Touch Screen

Type	Projection multi touch capacitive touch screen
Control interface	USB
Surface hardness	≥7H
Glass cover	AG AF
Transmittance	80%

I/O Connectors

USB	1 x USB2.0
Display	1 x VGA 1 x DVI 1 x HDMI/DP
Others	1 x DC-IN (2-Pin Phoenix)

Power Specification

Power Input	DC 12~24V
Power Adapter	AC-DC, 12V@5A, 60W
Power Consumption	19W(Typ.)

Environmental

Operating Temperature	-10~50°C
Storage Temperature	-20~60°C
Relative Humidity	10%-90%, @ 40°C (non-condensing)
Vibration	5~500Hz, 0.026 G ² /Hz, 2.16 Grms, X, Y, Z, 1 hour per axis
Certifications	CE, FCC

Mechanical

Housing	Aluminum alloy panel, all-metal structure
Mounting Method	Panel-mount, VESA-mount
Dimension (W x L x H)	399.4x 249.4 x 46 mm
Weight	3.0Kg

Packing List

- 1 x DPM-1156G
- 1 x AC-DC power adapter
- 1 x USB control cable
- 1 x VGA data cable
- 1 x Fixed cable buckle
- 1 x Certificate
- 1 x Warranty Card
- 8 x Panel Mounting Buckles

Dimensions

