

DPM-1185

18.5", Capacitive / Resistive Touch Screen , Industrial Touch Display



Features

- 18.5" LCD Capacitive / Resistive Touch
- Compact Structure, Front Panel IP65
- All Metal Structure Design, Durable
- Support Panel and VESA Installation



Specifications

| Display | | Power Specification | |
|-------------------|---|-----------------------|--|
| Size | 18.5-inch | Power Input | DC 12~24V |
| Resolution | 1920 x 1080 | Power Adapter | AC-DC, 12V@5A, 60W |
| Viewing Angle | 85/85/80/80 | Power Consumption | 15W(Typ.) |
| Color Support | 16.7M | Environmental | |
| Brightness | 250 cd/m ² | Operating Temperature | -10~50°C |
| Contrast Ratio | 1000:1 | Storage Temperature | -20~60°C |
| Response Time | 3.6/1.4 (Typ.)(Tr/Td) ms | Relative Humidity | 10%-90%, @ 40°C (non-condensing) |
| Backlight | LED | Vibration | 5~500Hz, 0.026 G ² /Hz, 2.16 Grms, X, Y, Z, 1 hour per axis |
| Backlight Life | 30000h | Certifications | CE, FCC |
| Touch Screen | | Mechanical | |
| Type | Projection Multi Touch Capacitive Touch Screen 5-wire Resistive Touch Screen | Housing | Aluminum alloy panel, all-metal structure |
| Control Interface | USB | Mounting Method | Panel-mount, VESA-mount |
| Surface Hardness | ≥6H & 3H | Dimension (W x L x H) | 467.4 x 288 x 46 mm |
| Transmittance | 85% & 78% | Weight | 4.9Kg |
| I/O Connectors | | Packing List | |
| USB | 1 x USB2.0 | | 1 x DPM-1185 |
| Display | 1 x VGA | | 1 x AC-DC Power Adapter |
| | 1 x DVI | | 1 x USB Control Cable |
| | 1 x HDMI/DP | | 1 x Cable Buckle |
| Others | 1 x DC-IN (2-Pin Phoenix) | | 1 x Certificate |
| | | | 1 x Warranty Card |
| | | | 8 x Panel Mounting Buckles |

Dimensions

