

15" Fully Protected Panel PC with 6th Gen Intel® Core™ i5 Processor

Overview

The RPC-5150 is a 15" industrial-grade touch panel PC powered by a high-performance Intel® Core™ i5 processor, ideally suited for use in industrial HMI applications. With its modular, fanless, and shockproof design, the robust RPC-5150 is fully IP65 rated for dustproof and waterproof protection, ensuring extreme durability. The RPC series offers display screen options available in both 4:3 and 16:9 aspect ratios. Moreover, it comes equipped with M12 I/O connectors, empowering it to withstand even the harshest environments.

Features

- Intel® Core™ i5-6200U processor
- 15" panel PC with capacitive or resistive touch screen
- Sealed to full IP65 protection against water and dust
- M12 connectors for maximum protection against vibration, shock and dirt
- -10 to 50°C operating temperature



I/O Interfaces



Specifications

Display	
Size	15 inch
Touch Type	5-wire resistive touch Projected capacitive multi touch (optional)
Resolution	1024 x 768
Luminance	350 nits
Contrast Ratio	700:1
View Angles	89 (left), 89 (right), 89 (up), 89(down)
Color	16.7 M
System	
CPU	Intel® Core™ i5-6200U processor
Memory	DDR3L up to 16GB
Storage	mSATA up to 1TB
Graphics	Intel® HD graphics 520
BIOS	AMI
I/O Ports	
USB	2x USB2.0
Serial	2x COM (supports 2x RS232 or 1x RS232 and 1x RS485)
Ethernet	2x GbE LAN
Expansion Slot	
Mini PCIe	1x Full length Mini PCIe for mSATA, 1x Full length Mini PCIe for Wi-Fi or 4G
Antenna	2x SMA antenna holes
RF Communication	
Wi-Fi	Wi-Fi 802.11 a/b/g/n/ac (optional)
Cellular	4G/LTE (optional)
Bluetooth	BT4.0 (optional)
Power	
Button	Power on/off
DC Input	12 VDC
Power Consumption	25 W (Typ.)
Power Mode	ATX
Operating System	
Windows	Windows 7, Windows 10
Mechanical	
Dimensions (W x D x H)	366.5 x 290.5 x 64 mm (14.43 x 11.44 x 2.52 inches)
Weight (N.W.)	5.4 kg (11.91 lbs)
Mounting	VESA 100
Material	Aluminum and SGCC
Environment	
Operating Temperature	-10 to 50°C (14 to 122°F)
Storage Temperature	-40 to 80°C(-40 to 176°F)
Relative Humidity	10% to 95% @ 40°C (104°F), non-condensing
IP Rating	IP65 compliant
Packing List	
Packing List	RPC-5150 panel PC 2x M12 to RJ45 Ethernet cable 1x M12 to USB cable 2 x M12 to DB9 cable AC-DC power adapter AC power cord

Dimensions

